

OWNER

OWNER’S SERIAL No.
MANUFACTURERS SERIAL No.
MANUFACTURED BY
COUNTRY OF MANUFACTURE
COUNTRY OF APPROVAL

MATERIALS:
TANK SHELL STAINLESS STEEL -

mm
mm
mm

MIN. DESIGN THICKNESS:
CORROSION ALLOWANCE:
MANUFACTURING THICKNESS:
TANK ENDS STAINLESS STEEL -

mm
mm
mm
mm

MIN. DESIGN THICKNESS:
CORROSION ALLOWANCE:
MANUFACTURING THICKNESS:
MILD STEEL EQUIVALENT THK.
OPERATING SPECIFICATIONS:
TANK WORKING PRESSURE
TANK TEST PRESSURE
TANK EXTERNAL PRESSURE
SATURATED STEAM WORKING PRESSURE
STEAM TEST PRESSURE
STEAM HEATING AREA

bar
bar
bar
bar
bar
m²

DESIGN
TANK DESIGN CODE
TANK OPERATING TEMP. RANGE
METALLURGICAL DESIGN TEMP. RANG
TANK TYPE
INSPECTION AUTHORITY
WEIGHT/CAPACITY:
WATER CAPACITY @ 20°
TARE WEIGHT
MAXIMUM WEIGHT OF CONTENTS
MAXIMUM GROSS WEIGHT

°C to °C
°C to °C

L	U.S. gal
kg	lb
kg	lb
kg	lb

APPROVALS:
TYPE APPROVAL No.
UK DfT (IMDG)
RID/ADR
US DOT
T.C. IMPACT APPROVED ;

APPROVED FOR TRANSPORT UNDER CUSTOMS SEAL

APPROVAL No.	
MANUFACTURER’S SERIAL No.	
DESIGN TYPE	

CSC SAFETY APPROVAL

APPROVAL No.		
DATE MANUFACTURED		
MANUFACTURER’S SERIAL No.		
MAXIMUM GROSS WEIGHT	kg	lb
ALLOWABLE STACKING WEIGHT FOR 1,8g	kg	lb
RACKING TEST LOAD VALUE	kg	lb
NEXT EXAMINATION DATE		

TESTS:

INITIAL HYDRAULIC TEST DATE					
2,5 yr INSPECTION DATE					
5 yr TEST DATE					

APPLICABLE PRODUCTS: FROM CLASSES 3, 4, 5.1, 6.1, 8 & 9
OPERATOR’S RESPONSIBILITY TO CHECK PRIOR TO LOADING