OWNER

APPROVED FOR TRANSPORT UNDER CUSTOMS SEAL

APPROVAL No.	
MANUFACTURER'S SERIAL No.	
DESIGN TYPE	

CSC SAFETY APPROVAL

APPROVAL No.		
DATE MANUFACTURED		
MANUFACTURER'S SERIAL No.		
MAXIMUM GROSS WEIGHT	kg	lb
ALLOWABLE STACKING WEIGHT FOR 1,8g	kg	lb
RACKING TEST LOAD VALUE	kg	lb
NEXT EXAMINATION DATE		

TESTS:

INITIAL HYDRAULIC TEST DATE

2,5 yr INSPECTION DATE

5 yr TEST DATE

APPLICABLE PRODUCTS: FROM CLASSES 3, 4, 5.1, 6.1, 8 & 9
OPERATOR'S RESPONSIBILITY TO CHECK PRIOR TO LOADING

OWNER'S SERIAL No.	
MANUFACTURERS SERIAL No.	
MANUFACTURED BY	
COUNTRY OF MANUFACTURE	
COUNTRY OF APPROVAL	

MATERIALS:

TANK SHELL STAINLESS STEEL -	
MIN. DESIGN THICKNESS:	mm
CORROSION ALLOWANCE:	mm
MANUFACTURING THICKNESS:	mm
TANK ENDS STAINLESS STEEL -	
MIN. DESIGN THICKNESS:	mm
CORROSION ALLOWANCE:	mm
MANUFACTURING THICKNESS:	mm
MILD STEEL EQUIVALENT THK.	mm

OPERATING SPECIFICATIONS:

TANK WORKING PRESSURE	bar
TANK TEST PRESSURE	bar
TANK EXTERNAL PRESSURE	bar
SATURATED STEAM WORKING PRESSURE	bar
STEAM TEST PRESSURE	bar
STEAM HEATING AREA	m²

DESIGN

TANK DESIGN CODE	
TANK OPERATING TEMP. RANGE	ºC to ºC
METALLURGICAL DESIGN TEMP. RANG	ºC to ºC
TANK TYPE	
INSPECTION AUTHORITY	

WEIGHT/CAPACITY:

WATER CAPACITY @ 20º	L	U.S. gal
TARE WEIGHT	kg	lb
MAXIMUM WEIGHT OF CONTENTS	kg	lb
MAXIMUM GROSS WEIGHT	kg	lb

APPROVALS:

TYPE APPROVAL No.	
UK DfT (IMDG)	
RID/ADR	
US DOT	
T.C. IMPACT APPROVED ;	